PRODUCT DATA SHEET 21 SERIES

GLOW IN THE DARK



web: https://stairnosingaustralia.com.au Contact: Daphne 0422 803 365

email: daphne@stairnosingaustralia.com.au

(c) Stair Nosing Australia



STAIR

STAIRNOSING 21 series-stair nosing is suitable for all level hard surfaces

This stair nosing fully complies with the requirements of AS 1428.1-2021 revised June Design for Access and Mobility. This architectural grade alloy offers good surface finish and superior corrosion resistance.

SPECIFICATIONS

PRODUCT	21 series glow in the dark
BASE MATERIAL	Stair nosing is extruded from 6063/T5 Alloy
FINISH	Clear Anodised – 25Um
TREAD WIDTH	75 mm
FRONT DEPTH	10 mm
GLOW STRIP WIDTH	Glow strip of 12 mm
INSERT TYPE	Carborundum– PVC and Ripple Trim
PRODUCT WARRANTY	2 Years
INSERT SLIP RATING	P4 & P5 Classification (Highest available)
CODE COMPLIANCE	AS1428.1-2009 Check floor finish colour for luminance
	contrast requirements
FIXING METHOD	assisted with adhesive fix
APPLICATION	Surface mounted on hard floor finishes - Concrete, Timber etc.

Inserts for 21 series




Photo-Luminescent Data Based on DIN 67510-1, 1000LX, D65 light source, excitation 5 min.

Photo Luminscent Insert

① 10min >1000mcd/sqm

② 60min >150mcd/sqm

Temperature resistance:

① -4 +/- 1 deg. C no peeling and cracks


② 50+/- 1 deg. C no peeling and cracks

The luminous strip is made of acrylic material

PVC ANTI SLIP STRIP



SOLID CARBORUNDUM



ALUMINIUM RIPPLE TRIM

