

PRODUCT DATA SHEET BRASS SCREW DOWN STUD

web: [https:// stairnosingaustralia.com.au](https://stairnosingaustralia.com.au)

Contact : Daphne 0422 803 36

email: daphne@stairnosingaustralia.com.au

BRASS STUDS


Tactiles series are designed to be installed onto pedestrian surfaces to assist in the orientation of people who are vision impaired and to give tactile warning to safely navigate around in a built environment - detectable underfoot or by cane.

SPECIFICATIONS

PRODUCT	Brass screw down Stud
CODE	NBS30
MATERIAL	Cozzosion Resistance Grade D2 Brass
TOP PROFILE	Concentric rings, plain sides
OVERALL DIMENSIONS	35mm x 5mm
PRODUCT WARRANTY	5 years (As per Standard Warranty)
SLIP RATING	R13
CODE COMPLIANCE	AS/NZS1428.4.1:2009, BCA 2014 (Subject to surrounding floor finish luminance)
FIXING METHOD	Screw down



PROFILE



A	35mm
B	5mm

LRV: Dry 48.74 Wet 49.03
Contrast required is 45%

LRV [Light Reflective Values] Luminance Contrast, values must be tested against adjacent surfaces for compliance with Australian Standards



STANDARD COLOURS

Finish



BRASS

TYPICAL INSTALLATION

Screw down

