

## PRODUCT DATA SHEET POLY DIRECTIONAL TILE

web: https:// stairnosingaustralia.com.au

6ontact : Daphne 0422 803 36

## email: daphne@stairnosingaustralia.com.au

## POLY TILE - DIRECTIONAL Tactiles series are designed to be installed onto pedestrian surfaces to assist in the orientation of people who are vision impaired and to give tactile warning to safely navigate around in a built environment - detectable underfoot or by cane. **SPECIFICATIONS** PRODUCT Poly tile Directional NRTD CODE MATERIAL High Impact Thermoprene (Poly) TOP PROFILE Directional bars OVERALL DIMENSIONS 300 x 300mm PLATE THICKNESS 2.6mm with bevelled edges PRODUCT WARRANTY 3 years (As per Standard Warranty) SLIP BATING V Rating PROFILE CODE COMPLIANCE AS/NZS1428.4.1:2009, BCA 2014 (Subject to surrounding floor finish luminance FIXING METHOD Heavy duty external grade butyl tape with reinforement mesh А 300mm Adhesive back for peel-n-stick fast application FEATURE (Shown in profile) В 2.6mm \* Length is 300mm STANDARD COLOURS Directional tile Required Contrast-30% TYPICAL INSTALLATION LRV [Light Reflective Values ] Luminance Contrast, values must be Fix with adhesive tested against adjacent surfaces for compliance with Australian Standards BLACK NRTD1001 YELLOW NRTD1002 GREY NRTD1003 MAX 300mr WHITE NRTD1004 BLUE NRTD1005 RED NRTD1006 YEARS Concrete Substrate TEBACOTTA NBTD1007 BEIGE NRTD1008

\* For porous surfaces primer may be required